



Xiamen Xing Yuan Zhou Industrial Co.,Ltd

1903# Dexin Building No.584 Xianyue Road, Xiamen, China

Web: <http://marscn.com> Email: info@marscn.com

Tel: 0086-592-5123699 Fax:0086-592-5123896

MS823 Tracked Excavator



Superior Feature

1. Advanced ESS power model control system meets the requirement of all kinds of operation conditions.
2. Effective and reliable negative flow hydraulic system, man-machine-in-one operation feeling.
3. Genuine ISUZU engine, low fuel consumption, high reliability, powerful engine, high operation efficiency, cost-save short construction period.
4. Reinforced boom & arm ensure powerful digging, especially suit rough operation.



Xiamen Xing Yuan Zhou Industrial Co.,Ltd

1903# Dexin Building No.584 Xianyue Road, Xiamen, China

Web: <http://marscn.com> Email: info@marscn.com

Tel: 0086-592-5123699 Fax:0086-592-5123896

5. The 3-stage air filter reduces the weariness of cylinder & especially suit the heavy dust operation condition.
6. Easy operation, convenient maintenance and repairing.
7. Superior capacity of tool kit.

Technical Parameter of MS823 Tracked Excavator

Working Range

Type	MS823
Max. cutting height	9680mm
Max. dumping height	6786mm
Max. digging depth	6940mm
Max. vertical wall digging depth	6100mm
Max. digging reach	10290mm
Max. digging reach on ground	10110mm
Min. swing radius	3935mm
8'Max. digging depth (8' level)	6740mm

Overall dimension

Type	MS823
Overall width of superstructure	2890mm
Overall height of cab	3020mm
Tail swing radius	2930mm
Overall width	2990mm
Overall length	10140mm
Overall height of boom	3100mm
Track gauge	2390mm
Shoe width	600mm
Undercarriage width	2990mm
Tumble length	3460mm
Track length	4260mm



Xiamen Xing Yuan Zhou Industrial Co.,Ltd

1903# Dexin Building No.584 Xianyue Road, Xiamen, China

Web: <http://marscn.com> Email: info@marscn.com

Tel: 0086-592-5123699 Fax:0086-592-5123896

Min. ground clearance	460mm
Specification	
Operation Weight	23500kg
Power	125kw/2100rpm
Capacity of Bucket	1.05m ³
Maximum Digging Force	150KN
Travel Speed	5.5/3.2 km/h
Grade ability	35°
Pressure to the Ground	50kpa
Swing Speed of Plarform	11.5rpm

[For more models information](#)

[For more products information](#)

[Visit our website](#)