



## Xiamen Xing Yuan Zhou Industrial Co.,Ltd

---

1903# Dexin Building No.584 Xianyue Road, Xiamen, China

Web: <http://marscn.com> Email: info@marscn.com

Tel: 0086-592-5123699 Fax:0086-592-5123896

### MS918 Wheel Loader



#### **Choosing our MS918, you can enjoy:**

1. Strong working capacity with voluminous bucket, shoveling in good performance.
2. Reliable engine durability-----good starting performance, big torque reserves coefficients.
3. Engine, torque converter, transmission case separated layout, easy for your maintenance.
4. Full hydraulic steering system, easy for your staff to operate
5. Original water-drop type pin, more solid and durable.
6. Torque converter in simple structure, high efficiency driving.



# Xiamen Xing Yuan Zhou Industrial Co.,Ltd

1903# Dexin Building No.584 Xianyue Road, Xiamen, China

Web: <http://marscn.com> Email: info@marscn.com

Tel: 0086-592-5123699 Fax:0086-592-5123896

7. Single pump priority confluence of the hydraulic valve system to enhance the working speed of boom.
8. Modeling of hood appearance for beauty and convenient maintenance.

### Optional Parts:

1. Bucket: standard bucket, stone bucket, bulk blade bucket
2. Multi-operation devices (texturing machine)-loader, side-dumping loader
3. Anti-rollover frame
4. Air conditioner: heating devices, cooling devices, heating/cooling devices

### Optional engine

Cummins 4BT3.9-C80 60kw/2000r/mi

Technical Parameter of MS918 Wheel Loader				
Operation weight		5750kg	Length	5820mm
Rated power		56kw	Height	2830mm
Bucket capacity		1.0m <sup>3</sup>	Width	1900mm
Rated load		1.8t	Bucket width	1950mm
Travelling speeds	Forward 1	0-9km/h	Dumping Height	2750mm
	Forward 2	0-22km/h	Dumping reach	895mm
	Reverse 1	0-9km/h	Engine model	SL4105ABK
	Reverse 2	0-22km/h	Maximum torque	≥221.9N.m
Maximum gradeability		30°	Rated output	2400r/min
Turning angle		35°±1°	Promote time of bucket	≤5s
Min. turning radius	The outer of wheel	4750mm	Hydraulic cycle time	≤10s
	The outer of bucket	5230mm	Tires specification	16/70-20
Min. ground clearance		279mm	Wheel base	2100mm
Breakout force		55KN	Tires width	1490mm

[For more models information](#)

[For more products information](#)

[Visit our website](#)