

Concrete Mixer Truck(Tank capacity-10m³)

项目 Items	车型 Vehicle	Concrete Mixer Truck(10m ³)
外形尺寸 (长×宽×高) Overall Dimension (mm)		9800×2495×3830
底盘型号 Chassis Model		HOWO
车辆总质量 Max. Gross Weight (kg)		31000
整车整备质量 Curb Weight (kg)		15650
轴距 1 Wheel Base1 (mm)		3200
轴距 2 Wheel Base2 (mm)		1350
轮距 Track 前轮 Front Wheel (mm)		2022
轮距 Track 后轮 (双轮中心线距离) Rear Wheel (mm)		1830
轮胎 Tire		12.00-20
前悬 Front Overhang (mm)		1500
后悬 Rear Overhang (mm)		1997
最小转弯半径 Mini.Turning Radius (m)		11.5
最高车速 (满载) Max. Speed (Loading) (km/h)		90
转向器 (德国) Steering Device(Germany)		ZF8098
百公里油耗 Oil Consumption within 100 Kilometers (L)		38
发动机 Engine		WD615.95 6 Cylinder, In-line, Water Cooling
发动机最大输出功率 Max.Engine Output (kw)		247(2200r/min)
发动机最大输出扭矩 Max.Engine Torque (N. M)		1350(1300-1600)
PTO 输出 PTO Output (N. M)		600(2200r/min)
搅拌筒搅动/几何容积 Agitator Mixing/Geometrical		17.05
搅拌容积 Agitator Mixing Capacity(m ³)		10
搅拌筒倾角 Agitator Inclined Angle (°)		12
搅拌筒转速 Agitator Rotation Speed (r/min)		0-14
进料速度 Feeding Speed (m ³ /min)		≥3.5
出料速度 Outlet Speed (m ³ /min)		≥3
坍落度 Landslide Degree (mm)		100-230
残余率 Surplus Rate (%)		0
水箱容积 Water Tank Volume (L)		400

Concrete Mixer Truck(Tank capacity-12m³)

项目 Items	车型 Vehicle	Concrete Mixer Truck(12 m ³)
外形尺寸 (长×宽×高) Overall Dimension (mm)		9880×2496×3920
底盘型号 Chassis Model		HOWO
车辆总质量 Max. Gross Weight (kg)		25000
整车整备质量 Curb Weight (kg)		15000
轴距 1 Wheel Base1 (mm)		4025
轴距 2 Wheel Base2 (mm)		1350
轮距 Track 前轮 Front Wheel (mm)		2022
轮距 Track 后轮 (双轮中心线距离) Rear Wheel (mm)		1830
轮胎 Tire		12.00-20
前悬 Front Overhang (mm)		1500
后悬 Rear Overhang (mm)		3005
最小转弯半径 Mini.Turning Radius (m)		11.5
最高车速 (满载) Max. Speed (Loading) (km/h)		86
转向器 (德国) Steering Device(Germany)		ZF8098
百公里油耗 Oil Consumption within 100 Kilometers (L)		38
发动机 Engine		WD615.95 6 Cylinder, In-line, Water Cooling
发动机最大输出功率 Max.Engine Output (kw)		247(2200r/min)
发动机最大输出扭矩 Max.Engine Torque (N. M)		1350(1300-1600)
PTO 输出 PTO Output (N. M)		600(2200r/min)
搅拌筒搅动/几何容积 Agitator Mixing/Geometrical		19.35
搅拌容积 Agitator Mixing Capacity(m ³)		12
搅拌筒倾角 Agitator Inclined Angle (°)		11
搅拌筒转速 Agitator Rotation Speed (r/min)		0-14
进料速度 Feeding Speed (m ³ /min)		≥3.5
出料速度 Outlet Speed (m ³ /min)		≥3
坍落度 Landslide Degree (mm)		100-230
残余率 Surplus Rate (%)		0
水箱容积 Water Tank Volume (L)		400

Concrete Mixer Truck(Tank capacity-14m³)

项目 Items	车型 Vehicle	Concrete Mixer Truck(14 m ³)
外形尺寸 (长×宽×高) Overall Dimension (mm)		10300×2496×3950
底盘型号 Chassis Model		HOWO
车辆总质量 Max. Gross Weight (kg)		31000
整车整备质量 Curb Weight (kg)		16000
轴距 1 Wheel Base1 (mm)		1800+3200+1350
轴距 2 Wheel Base2 (mm)		
轮距 Track 前轮 Front Wheel (mm)		2022
轮距 Track 后轮 (双轮中心线距离) Rear Wheel (mm)		1830
轮胎 Tire		12.00-20
前悬 Front Overhang (mm)		1500
后悬 Rear Overhang (mm)		2450
最小转弯半径 Mini.Turning Radius (m)		11.5
最高车速 (满载) Max. Speed (Loading) (km/h)		90
转向器 (德国) Steering Device(Germany)		ZF8098
百公里油耗 Oil Consumption within 100 Kilometers (L)		38
发动机 Engine		WD615.95 6 Cylinder, In-line, Water Cooling
发动机最大输出功率 Max.Engine Output (kw)		247(2200r/min)
发动机最大输出扭矩 Max.Engine Torque (N. M)		1350(1300-1600)
PTO 输出 PTO Output (N. M)		600(2200r/min)
搅拌筒搅动/几何容积 Agitator Mixing/Geometrical		20.1
搅拌容积 Agitator Mixing Capacity(m ³)		14
搅拌筒倾角 Agitator Inclined Angle (°)		12
搅拌桶转速 Agitator Rotation Speed (r/min)		0-14
进料速度 Feeding Speed (m ³ /min)		≥3.5
出料速度 Outlet Speed (m ³ /min)		≥3
坍落度 Landslide Degree (mm)		100-230
残余率 Surplus Rate (%)		0
水箱容积 Water Tank Volume (L)		400

Concrete Mixer Truck(Tank capacity-16m³)

项目 Items	车型 Vehicle	Concrete Mixer Truck(16m ³)
外形尺寸 (长×宽×高) Overall Dimension (mm)		10850×2496×3980
底盘型号 Chassis Model		HOWO
车辆总质量 Max. Gross Weight (kg)		31000
整车整备质量 Curb Weight (kg)		17000
轴距 1 Wheel Base1 (mm)		1800+3600+1350
轴距 2 Wheel Base2 (mm)		
轮距 Track 前轮 Front Wheel (mm)		2022
轮距 Track 后轮 (双轮中心线距离) Rear Wheel (mm)		1830
轮胎 Tire		12.00-20
前悬 Front Overhang (mm)		1500
后悬 Rear Overhang (mm)		2600
最小转弯半径 Mini.Turning Radius (m)		12.1
最高车速 (满载) Max. Speed (Loading) (km/h)		90
转向器 (德国) Steering Device(Germany)		ZF8098
百公里油耗 Oil Consumption within 100 Kilometers (L)		38
发动机 Engine		WD615.95 6 Cylinder, In-line, Water Cooling
发动机最大输出功率 Max.Engine Output (kw)		276(2200r/min)
发动机最大输出扭矩 Max.Engine Torque (N. M)		1350(1300-1600)
PTO 输出 PTO Output (N. M)		600(2200r/min)
搅拌筒搅动/几何容积 Agitator Mixing/Geometrical		24.1
搅拌容积 Agitator Mixing Capacity(m ³)		16
搅拌筒倾角 Agitator Inclined Angle (°)		10
搅拌筒转速 Agitator Rotation Speed (r/min)		0-14
进料速度 Feeding Speed (m ³ /min)		≥3.5
出料速度 Outlet Speed (m ³ /min)		≥3
坍落度 Landslide Degree (mm)		100-230
残余率 Surplus Rate (%)		0
水箱容积 Water Tank Volume (L)		400